



**A-53** Arizona Tan



**A-59** Beige Cream\*



**A-26** Brick Red



**A-33** Classic Gray



**A-21** Deep Charcoal



**A-25** La Crescenta Brown



**A-57** Platinum Gray




**A-50** Slate Gray



**A-51** Steadman Buff



**A-29** Terra Cotta



**5921** Walnut



**1290** Cordovan Brown

**COVERAGE RATE FOR COLOR HARDENER:** Coverage rates vary with intended use and application. LITHOCHROME Color Hardener should be applied at a rate of 60 lb (1 bag) per 100 ft<sup>2</sup> (3.0 kg/m<sup>2</sup>), except where indicated by an asterisk (\*).

\*Denotes colors requiring a higher coverage rate, where Scofield recommends 90–120 lb per 100 ft<sup>2</sup> (4.5–6.0 kg/m<sup>2</sup>). See reverse for more information.

+\$\$ = Check current market price.

Colors are approximate and best viewed in daylight. Colors shown represent the use of LITHOCHROME Color Hardener with a flat-troweled finish which has been cured with color-matched LITHOCHROME Colorwax or COLORCURE Concrete Sealer.

L. M. Scofield Company 1 800 800 9900

**FOR PROFESSIONAL USE ONLY**

2013 PMM

